

## Accessories

### ZB 4

**Weidmüller Interface GmbH & Co. KG**  
 Klingenbergstraße 16  
 D-32758 Detmold  
 Germany  
 Fon: +49 5231 14-0  
 Fax: +49 5231 14-292083  
 www.weidmueller.com



In the switching facilities and controllers, the N conductor may need to be merged with the PE conductor at a central point. For this reason, busbars are available that allow a wide range of cables to be connected within a confined space (up to 70 wires on one metre of rail). The cables are connected via a compression piece or a clamping yoke. For the first variant there is no need to bend the lugs. A guide lug at the compression piece grips into the busbar and holds tightly to the compression piece. The clamping yokes can be moved on the busbar and adjusted to the whole wiring in the facility. The busbar can be used without holes in various lengths. The rail holding clamp SH is used for fastening. On longer rails, it can also be aligned between clamping yokes.

#### General ordering data

Order No.	<a href="#">0316500000</a>
Type	ZB 4
Version	Accessories, Clamping yoke for busbar, Rated cross-section: Clamping yoke
GTIN (EAN)	4008190061999
Qty.	50 pc(s).

**Accessories  
ZB 4**

**Weidmüller Interface GmbH & Co. KG**  
 Klingenbergstraße 16  
 D-32758 Detmold  
 Germany  
 Fon: +49 5231 14-0  
 Fax: +49 5231 14-292083  
 www.weidmueller.com

**Technical data**
**Dimensions and weights**

Length	16 mm	Width	5.6 mm
Height of lowest version	12 mm	Net weight	2.98 g

**Temperatures**

Operating temperature	Storage temperature
-----------------------	---------------------

**Rated data IECEx/ATEX**

ATEX certificate	DEMKO03ATEX136028U_d.pdf	ATEX certificate	DEMKO03ATEX136028U_e.pdf
Voltage, cross-connection	CrossConnectionGuide.pdf	Operating temperature range	For operating temperature range see EC Design Test Certificate / IEC Ex-Certificate of Conformity
Marking ATEX Directive 94/9/EC	II 2 G D		

**Additional technical data**

Version	15 x 6 mm busbar connection
---------	-----------------------------

**CSA ratings data**

Certificate No. (CSA)	12400-237	Wire cross section max. (CSA)	10 AWG
Wire cross section min. (CSA)	26 AWG		

**Clampable wires (rated connection)**

Type of connection	Clamping yoke
--------------------	---------------

**Dimensions**

TS 35 offset	39 mm
--------------	-------

**UL ratings data**

Certificate No. (UR)	E60693VOL1SEC45	Conductor size Factory wiring max. (UR)	12 AWG
Conductor size Factory wiring min. (UR)	20 AWG	Conductor size Field wiring max. (UR)	12 AWG

**Material data**

Material	Steel	Colour	Silver
----------	-------	--------	--------

**System specifications**

Product family	Accessories	Type of connection	Clamping yoke
Mounting rail	TS 35		

**Classifications**

ETIM 2.0	EC000001	ETIM 3.0	EC000001
UNSPSC	30-21-18-11	eClass 4.1	27-14-11-31
eClass 5.1	27-14-11-31	eClass 6.0	27-14-11-90
eClass 7.0	27-14-11-90		

**Accessories  
ZB 4**

**Weidmüller Interface GmbH & Co. KG**  
Klingenbergstraße 16  
D-32758 Detmold  
Germany  
Fon: +49 5231 14-0  
Fax: +49 5231 14-292083  
www.weidmueller.com

**Technical data****Rated data IECEx/ATEX**

## Safety notice

## Installation instructions:

The potential equalisation (PE) rail modules are suitable for use in housings in atmospheres with flammable gases and dust. For use in areas with flammable gases, these housings must meet the requirements of EN 60079-0 and EN 60079-7. For use in areas with flammable dust, these housings must meet the requirements of EN 60079-0 and EN 60079-31.

When combined with other terminal block ranges and sizes, and when other accessories are used, you must comply with the clearance and creepage distances given.

Regarding accessory use, the manufacturer's instructions must be followed.

## List of restrictions:

The PE rail modules are considered one component, with Ex marking when used with the busbar holders of type SH and WEW. When used independently, the above named components are not covered by this certificate.

**Approvals**

## Approvals

**Downloads**

DXF [41547\\_ZB\\_4\\_DXF.dxf](#)

[3-D model](#)