

## Klippon Klippon POK 5

**Weidmüller Interface GmbH & Co. KG**  
 Klingenbergstraße 16  
 D-32758 Detmold  
 Germany  
 Fon: +49 5231 14-0  
 Fax: +49 5231 14-292083  
 www.weidmueller.com



**Polyester housings** The glass fibre-reinforced polyester housings of the Klippon POK series represent a high-quality, inexpensive solution for electric connections. These enclosures are ideal wherever corrosion resistance, shock resistance and a high class of protection are required.

Features:

- 17 sizes
- Cover with stainless steel screws
- fixing holes outside the sealed area
- Thread for fitting to terminal rails and mounting plates
- Weidmüller can manufacture and supply this enclosure to match customer specifications, fitted with all necessary terminals and cable glands.

### General ordering data

Order No.	<a href="#">1277600000</a>
Type	Klippon POK 5
Version	Klippon-Protected component assemblies, Enclosures, Glass fibre-reinforced polyester, 120 mm, 91 mm, 220 mm
GTIN (EAN)	4008190167882
Qty.	1 pc(s).

**Klippon**  
**Klippon POK 5**

**Weidmüller Interface GmbH & Co. KG**  
 Klingenbergstraße 16  
 D-32758 Detmold  
 Germany  
 Fon: +49 5231 14-0  
 Fax: +49 5231 14-292083  
 www.weidmueller.com

**Technical data****Dimensions and weights**

Length	91 mm	Width	220 mm
Height	120 mm	Mounting dimension - width	204 mm
Mounting dimension - height	82 mm	Weight	1,060 g
Net weight	1,200 g		

**Cable glands, right**

M12 (2)	8	M16 (2)	4
M20 (2)	3	M25 (2)	1
M32 (2)	1	Side of enclosure	left, top, right, Bottom

**Cable glands, top/bottom**

M12	24	M16	14
M20	12	M25	5
M32	4	M40	3
Side of enclosure	left, top, right, Bottom		

**General information**

Areas of use	Transportation, Harbour facilities, Process industry	UL 94 flammability rating	V-0
Material	Glass fibre-reinforced polyester	Seal material	Chloroprene
Surface finish	untreated	Colour code	RAL 7001
Operating temperature, min.	-40 °C	Operating temperature, max.	100 °C
Impact resistance	7.00 J	Protection degree	IP 66
Enclosure attachment	Holes 6 mm	Cover attachment	M6 slotted and crosshead stainless steel screws

**General information on accessories**

Material	Glass fibre-reinforced polyester	Mounting dimension - height	82 mm
Mounting dimension - width	204 mm	Surface finish	untreated

**horizontal assembly**

WDU 10 / ZDU 10	1x15	WDU 16 / ZDU 16	1x13
WDU 2,5 / ZDU 2,5 / IDU 2,5	1x31	WDU 4 / ZDU 4	1x26
WDU 6 / ZDU 6	1x19		

**vertical assembly**

WDU 10 / ZDU 10 (2)	*	WDU 16 / ZDU 16 (2)	*
WDU 2,5 / ZDU 2,5 / IDU 2,5 (2)	*	WDU 4 / ZDU 4 (2)	*
WDU 6 / ZDU 6 (2)	*		

**Classifications**

ETIM 2.0	EC000058	ETIM 3.0	EC000058
UNSPSC	31-26-15-02	eClass 4.1	27-14-12-06
eClass 5.1	27-14-91-07	eClass 6.0	27-14-91-07
eClass 7.0	27-14-91-07		

**Klippon  
Klippon POK 5**

**Weidmüller Interface GmbH & Co. KG**  
Klingenbergstraße 16  
D-32758 Detmold  
Germany  
Fon: +49 5231 14-0  
Fax: +49 5231 14-292083  
www.weidmueller.com

**Technical data**

**Test certificates**

Certificate No. (MARITREG) 09.04041.250

**Approvals**

Approvals



**Data sheet...**

**Klippon**  
**Klippon POK 5**

**Weidmüller Interface GmbH & Co. KG**  
Klingenbergstraße 16  
D-32758 Detmold  
Germany  
Fon: +49 5231 14-0  
Fax: +49 5231 14-292083  
[www.weidmueller.com](http://www.weidmueller.com)

**Drawings**

