

**SAK Series
QVS 2/4 SAKT4**

Weidmüller Interface GmbH & Co. KG
Klingenbergstraße 16
D-32758 Detmold
Germany
Fon: +49 5231 1429-0
Fax: +49 5231 14292083
www.weidmueller.com

**Current and voltage transformer wiring**

Our test disconnect terminal blocks featuring spring and screw connection technology allow you to create all the important converter circuits for measuring current, voltage and power in a safe and sophisticated way.

General ordering data

Type	QVS 2/4 SAKT4
Order No.	1319260000
Version	SAK Series, Cross-connector, Cross-connector, No. of poles: 2
GTIN (EAN)	4008190136512
Qty.	20 pc(s).

Data sheet

SAK Series QVS 2/4 SAKT4

Weidmüller Interface GmbH & Co. KG
 Klingenbergstraße 16
 D-32758 Detmold
 Germany
 Fon: +49 5231 1429-0
 Fax: +49 5231 14292083
 www.weidmueller.com

Technical data

Dimensions and weights

Width	11 mm	Width (inches)	0.433 inch
Height	22.3 mm	Height (inches)	0.878 inch
Depth	10.5 mm	Depth (inches)	0.413 inch
Net weight	0.767 g		

Temperatures

Operating temperature range, max.	100 °C	Continuous operating temp., min.	-50 °C
Continuous operating temp., max.	100 °C		

Material data

Material	PA 66	Colour	Beige
UL 94 flammability rating	V-2		

System specifications

Version	Cross-connector	Mounting rail	none
---------	-----------------	---------------	------

Additional technical data

Explosion-tested version	No	Type of fixing	Screwed
Type of mounting	Clamped		

Dimensions

Pitch in mm (P)	12 mm	TS 35 offset	45.5 mm
-----------------	-------	--------------	---------

Classifications

ETIM 3.0	EC000489	ETIM 4.0	EC000489
ETIM 5.0	EC000489	ETIM 6.0	EC000489
UNSPSC	30-21-18-01	eClass 5.1	27-14-11-40
eClass 6.2	27-14-11-40	eClass 7.1	27-14-11-40
eClass 8.1	27-14-11-40	eClass 9.0	27-14-11-40
eClass 9.1	27-14-11-40		

Approvals

ROHS	Conform
------	---------

Downloads

Brochure/Catalogue	CAT 1 TERM 16/17 EN
--------------------	-------------------------------------