

Terminal markers WS 8/5 MC NE WS

Weidmüller Interface GmbH & Co. KG
 Klingenbergstraße 16
 D-32758 Detmold
 Germany
 Fon: +49 5231 14-0
 Fax: +49 5231 14-292083
 www.weidmueller.com



WS markers are the perfect match for the W-series connectors. Thanks to their system compatibility, the WS tags can also be used with the I-series and the Z-series. The large marking surfaces do not only permit long character strings but also multi-line text. WS markers are ideal for labels with long, customised character strings. Thanks to the proven MultiCard format, printing with laser printer, PrintJet ADVANCED, plotter or MC-Mobilo is possible.

- Can be fitted in strips or individually
- Markers in proven MultiCard format

General ordering data

| | |
|------------|--|
| Type | WS 8/5 MC NE WS |
| Order No. | 1640740000 |
| Version | Terminal markers, MultiCard, 8 x 5 mm, Polyamide 66, Colour: White |
| GTIN (EAN) | 4008190279103 |
| Qty. | 720 pc(s). |

Data sheet

**Terminal markers
WS 8/5 MC NE WS**

Weidmüller Interface GmbH & Co. KG
 Klingenbergstraße 16
 D-32758 Detmold
 Germany
 Fon: +49 5231 14-0
 Fax: +49 5231 14-292083
 www.weidmueller.com

Technical data

Dimensions and weights

| | | | |
|------------|---------|-------|------|
| Length | 8 mm | Width | 5 mm |
| Net weight | 0.169 g | | |

General data

| | | | |
|-----------------------------------|---------------|--|--------|
| Application/manufacture | Allen-Bradley | Colour | White |
| Material | Polyamide 66 | Material colour according to resistance code | 9 |
| Operating temperature range, max. | 100 °C | Operating temperature range, min. | -40 °C |
| UL 94 flammability rating | V-2 | | |

Connector markers

| | |
|-----------------|------|
| Pitch in mm (P) | 5 mm |
|-----------------|------|

Classifications

| | | | |
|------------|-------------|------------|-------------|
| ETIM 3.0 | EC000761 | UNSPSC | 30-21-18-07 |
| eClass 5.1 | 27-14-11-37 | eClass 6.2 | 27-14-11-37 |
| eClass 7.1 | 27-14-11-37 | | |

Approvals

| | |
|------|---------|
| ROHS | Conform |
|------|---------|