

W-Series
WSI 25/2 CC

Weidmüller Interface GmbH & Co. KG
Klingenbergstraße 16
D-32758 Detmold
Germany
Fon: +49 5231 14-0
Fax: +49 5231 14-292083
www.weidmueller.com



The fuse terminals of the Weidmüller W Series are available in two different forms:

- Fuse terminal with pivoting retaining lever
- Fuse terminal with plug-in SIHA fuse holder

General ordering data

Type	WSI 25/2 CC
Order No.	1966040000
Version	W-Series, Fuse terminal, Rated cross-section: 25 mm ² , Screw connection
GTIN (EAN)	4032248657780
Qty.	6 pc(s).

W-Series
WSI 25/2 CC

Weidmüller Interface GmbH & Co. KG
 Klingenbergstraße 16
 D-32758 Detmold
 Germany
 Fon: +49 5231 14-0
 Fax: +49 5231 14-292083
 www.weidmueller.com

Technical data
Dimensions and weights

Length	58 mm	Width	36 mm
Height	58 mm	Height of lowest version	58 mm
Weight	131 g	Net weight	126.833 g

Temperatures

Operating temperature		Storage temperature	
Continuous operating temp., min.	-50 °C	Continuous operating temp., max.	120 °C

Additional technical data

Open sides	closed	Type of mounting	Snap-on
Version	Screw connection, Fuse cartridge, closed		

CSA ratings data

Certificate No. (CSA)	238018-1868186	Wire cross section max. (CSA)	4 AWG
Wire cross section min. (CSA)	18 AWG		

Clampable wires (rated connection)

Type of connection	Screw connection	Connection direction	on side
Number of connections	2	Clamping range, rated connection, min.	1.5 mm ²
Clamping range, rated connection, max.	25 mm ²	Tightening torque, min.	2 Nm
Tightening torque, max.	2.5 Nm	Wire connection cross section, solid core, max. rated connection	1.5 mm ²
Wire connection cross section, solid core max. rated connection	25 mm ²	Wire connection cross section, stranded, rated connection, min.	1.5 mm ²
Wire connection cross section, stranded, rated connection, max.	25 mm ²	Wire connection cross section, finely stranded, max.	25 mm ²
Wire connection cross-section, finely stranded, min.	1.5 mm ²	Wire connection cross section, finely stranded with wire-end ferrules DIN 46228/1, rated connection, min.	1.5 mm ²
Wire connection cross section, finely stranded with wire-end ferrules DIN 46228/1, rated connection, max.	25 mm ²	Cross-section for connected conductor, finely stranded with wire-end ferrules and plastic collars DIN 46228/4, rated connection, min.	1.5 mm ²
Wire connection cross-section, finely stranded with wire-end ferrules and plastic collars DIN 46228/4, rated connection, max.	25 mm ²	Wire connection cross section AWG, min.	AWG 18
Wire connection cross section AWG, max.	AWG 4		

Dimensions

TS 35 offset	40.5 mm
--------------	---------

Rated data

Rated cross-section	25 mm ²	Rated voltage to adjoining terminal	690 V
Rated impulse withstand voltage	6 kV	Rated current	32 A
Current at maximum wires	32 A	Standards	IEC 60947-7-3
Pollution severity	3		

**W-Series
WSI 25/2 CC**

Weidmüller Interface GmbH & Co. KG
 Klingenbergstraße 16
 D-32758 Detmold
 Germany
 Fon: +49 5231 14-0
 Fax: +49 5231 14-292083
 www.weidmueller.com

Technical data

Material data

Material	Wemid	Colour	Dark Beige
UL 94 flammability rating	V-0		

System specifications

Product family	W-Series	Type of connection	Screw connection
Connection direction	on side	Number of levels	1
Number of connections	2	No. of clamping points per level	2
Mounting rail	TS 35	End cover plate required	Yes

Fuse terminals

Cartridge fuse	max. 3W for gG/gL max. 1.2W for aM
----------------	---------------------------------------

Classifications

ETIM 3.0	EC000899	UNSPSC	30-21-18-01
eClass 6.2	27-14-11-16	eClass 7.1	27-14-11-16

Product information

Descriptive text technical data	Suitable for fuse cartridges to IEC 60269-6 with power loss up to 3 W maximum.
---------------------------------	--

Approvals

Approvals



ROHS	Conform
------	---------

Data sheet...

W-Series
WSI 25/2 CC

Weidmüller Interface GmbH & Co. KG
Klingenbergstraße 16
D-32758 Detmold
Germany
Fon: +49 5231 14-0
Fax: +49 5231 14-292083
www.weidmueller.com

Drawings

