

PLUGSERIES
PRZ 120Vac LD 2CO**Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 16

D-32758 Detmold

Germany

Fon: +49 5231 14-0

Fax: +49 5231 14-2083

www.weidmueller.com



High power/currents can be safely switched with the PLUGSERIES. The modular system enables conventional relays and LED indicators simply to be plugged in. Retaining and disassembly clips provide a secure mount.

Pre-assembled relays with 1 or 2 changeover contacts and input voltages from 24V to 230V round of the product range. Plug-in ZQV 2.5 cross-connectors enable relay multiplexers to be set up quickly thanks to simple side-by-side mounting.

General ordering data

Order No.	8530720000
Type	PRZ 120Vac LD 2CO
Version	PLUGSERIES, Relays, No. of contacts: 2, CO contact, Rated control voltage: 120 V AC \pm 10 %, Tension clamp connection
GTIN (EAN)	4032248163311
Qty.	10 pc(s).

PLUGSERIES
PRZ 120Vac LD 2CO

Weidmüller Interface GmbH & Co. KG
 Klingenbergstraße 16
 D-32758 Detmold
 Germany
 Fon: +49 5231 14-0
 Fax: +49 5231 14-2083
 www.weidmueller.com

Technical data
Dimensions

Length	92 mm	Width	15.3 mm
Height	87 mm		

Temperatures

Operating temperature	-40 °C...+50 °C	Ambient temperature (text)	-40 °C...+50 °C
Storage temperature	-40 °C...+85 °C		

Connection data

Wire connection cross section, finely stranded, max.	2.5 mm ²	Clamping range, rated connection	2.5 mm ²
Clamping range, rated connection, min.	0.5 mm ²	Clamping range, rated connection, max.	2.5 mm ²

Input

Power rating	1.1 VA	Rated control voltage	120 V AC ±10 %
Rated current AC	9.1 mA	Response / drop-out voltage AC coil	53 V / 49 V
Status indicator	Green LED		

Output

Continuous current	2 x 8 A	Max. switching current	16 A
Max. switching frequency at rated load	0.1 Hz	Max. switching power	2x2 kVA
Max. switching voltage, AC	250 V	Min. switching power	10 V / 100 mA
Sparkover time / Drop-out time	7.8 ms / 41.5 ms	Switch-off delay	< 45ms
Switch-on delay	9 ms	making current	2 x 8 A

Contact data

No. of contacts	2	Contact design	CO contact
Mechanical service life	5 x 10 ⁶ switching cycles	Type of contact	CO contact
Contact material	AgNi 90/10		

Rated data

Ambient temperature (text)	-40 °C...+50 °C	Conductor connection system	Tension clamp connection
Flammability class UL 94	V-0	Humidity	40 °C / 93% rel. humidity, no condensation
Relay type	SIEMENS RT 2	Wire cross-section, solid, max.	2.5 mm ²

Insulation coordination (EN 50 178)

Clearance and creepage distances for control side - load side	> 8 mm	Impulse withstand voltage	6 kV
Pollution severity	2	Protection degree	IP 20
Rated voltage	300 V AC _{eff}	Surge voltage category	III

Other technical data

Free-wheel diode	No	Reverse polarity protection	No
Status indicator	Green LED	Version	Relay coupler

**PLUGSERIES
PRZ 120Vac LD 2CO**

Weidmüller Interface GmbH & Co. KG
 Klingenbergstraße 16
 D-32758 Detmold
 Germany
 Fon: +49 5231 14-0
 Fax: +49 5231 14-2083
 www.weidmueller.com

Technical data

Approvals

Standards DIN EN 50178

Classifications

ETIM 2.0	EC001437	ETIM 3.0	EC001437
ETIM 4.0	EC001437	UNSPSC	30-21-19-17
eClass 4.1	40-02-06-14	eClass 5.1	27-37-16-01
eClass 6.0	27-37-16-01	eClass 7.0	27371601

Approvals

Approvals



Downloads

Declaration of Conformity [K217_09_09.pdf](#)
[3-D model](#)

**PLUGSERIES
PRZ 120Vac LD 2CO**

Weidmüller Interface GmbH & Co. KG
Klingenbergstraße 16
D-32758 Detmold
Germany
Fon: +49 5231 14-0
Fax: +49 5231 14-2083
www.weidmueller.com

Drawings**Electric symbol**