

## Accessories for Branch Circuit Breakers

Module	Type of Contact	Contacts	Weight g / Each	Packing Unit	Part No.
<b>Auxiliary contact, for mounting on the right</b>					
1/2	1 auxiliary contact	1NO	35	6	<b>BAU10</b>
1/2	2 auxiliary contacts	1NO + 1NC	40	6	<b>BAU11</b>



Standards	UL489 and CSA-22.2 Nr. 5-09	
Rated operating currents	10 A / 240 V AC	
	3 A / 110 V DC	
	1 A / 220 V DC	
Minimum contact load	1 mA at 24 V DC	
Conductor cross sections		
Type of conductor *)	min.	max.
Single wire	1.0 mm <sup>2</sup> (AWG18)	2.5 mm <sup>2</sup> (AWG14)
Stranded wire	1.0 mm <sup>2</sup> (AWG18)	1.5 mm <sup>2</sup> (AWG16)
Stranded wire with ferrule	1.0 mm <sup>2</sup> (AWG18)	1.5 mm <sup>2</sup> (AWG16)
Torque	max. 0.8 Nm (7 lb.in)	

\*) Stripped length 8 - 9 mm ( ) values in brackets = measurement units for North America



### Lock-off/Lock-on device

Weight g / Each	Packing Unit	Part No.
2	10	<b>LD10</b>