



GE
Industrial Solutions

[Advanced Search](#) | [Search Tips](#)

[Where to Buy](#) | [Contact Us](#) | [EliteNet](#)

Short Description: MMS HIGH BK 11 - 16 AMPS

[Buy Online!](#) | [My Cart](#)

SPECIFICATIONS

Category	Manual Motor Starter - SURION
Rated Current	16 A
Capacity	GPS1BH - High breaking capacity
Instantaneous short-circuit release (A)	208
Rated power 3 phase motors at 220/230Vac Pn (hp)	3
Rated power 3 phase motors at 400Vac Pn (hp)	5
Rated power 3 phase motors at 440Vac Pn (hp)	10
Rated power 3 phase motors at 500/525Vac Pn (hp)	10
Rated power 3 phase motors at 660/690Vac Pn (hp)	11 hp
Rated service short-circuit breaking cap 220/230V Ics kA	65
Rated service short-circuit breaking cap 400V Ics kA	50
Rated service short-circuit breaking cap 440V Ics kA	10
Rated service short-circuit breaking cap 500/525V Ics kA	8
Rated service short-circuit breaking cap 600V Ics kA	3
Rated service short-circuit breaking cap 690V Ics kA	3
Rated ultimate short-circuit breaking cap 220/230V Icu kA	65
Rated ultimate short-circuit breaking cap 400V Icu kA	25
Rated ultimate short-circuit breaking cap 440V Icu kA	25
Rated ultimate short-circuit breaking cap 500/525V Icu kA	10
Rated ultimate short-circuit breaking cap 600V Icu kA	4
Rated ultimate short-circuit breaking cap 690V Icu kA	4
Series	Surion - GPS1B -



- MANUAL MOTOR STARTER T+M PROT.
GPS1 11-16A HIGH BREAKING
- Pack-5

	Thermal and magnetic protection (Ie max 32A)
Thermal current setting range (A)	11 - 16 A
Trip class IEC 60947-4-1	Class 10
Weight	0.792 lb
Single Phase Horsepower @ 115V	1
Single Phase Horsepower @ 230V	2
FLA Adjustment Range	11 - 16 A
Max. Fuse Size (A)	60
Max Circuit Breaker Size (A)	60
Max. Fuse or Circuit Breaker Size - Group Installation (A)	500
Rated Breaking Capacity @ 277Y/480V - Combination Starter (kA)	50
Minimum Contactor Size	CL01
Width	45.0 mm
GSA Compliance	No
GO Schedule	10A2C
List Price	\$150

